

D195

Advanced MiniPOS



Food & Beverage



Fashion & Retail



Transportation



CLASSIC



Powered by Nuxiums



PCI 6 SRED



2.4" Display



0.3MP Front



Advanced Connectivity

D195

Nuxiums MiniPOS

SPECIFICATIONS

	Operating System	Nuxiums
	Processor	Cortex A5 800mHz
	Memory	128M Flash+128M DDR 256M Flash + 256M DDR (optional)
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Cameras	0.3MP (optional)
	Display	2.4" TFT QVGA 320 x 240 Pixels Optional Touch Screen
	Comms Configurations	Wi-Fi® 2.4GHz/5GHz Bluetooth 5.0(optional) 2G / 3G / 4G (optional) 4G (Cat-M) (optional) 4G Cat-1 (optional)
	Battery	1900mAh 3.7V
	Power Supply	Input: 100 - 240V AC, 50 / 60 Hz, 0.2A Output: 5V DC, 1A
	Durability-drop	1.5m ESD: contact 12KV, air 18KV
	SIM / SAM	1SIM + 1SAM 1eSIM (optional)
	Charging PogoPIN	2PIN(optional , supports Modular Charging Kit)
	Keys / Buttons	15 Keys: 0~9 F1 F2 Enter Clear Cancel
	Audio	1 Buzzer
	Ports	1 Type-C OTG
	Physical	129 x 71 x 17mm, 185g (including battery)
	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 6.x SRED EMV L1 & L2 Mastercard contactless Visa payWave American Expresspay Discover D-PAS BQB CE UL FCC IC Interact Flash L2 JCB CL QUICKPASS TQM UKCA RoHS



This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX and the PAX logo are either trademarks or registered trademarks of PAX Technology Inc. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology Inc. is under license. Other trademarks and trade names are those of their respective owners. © 2023 PAX Technology Inc. All rights reserved.

